

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

Claims 1-81 canceled.

Please add new claims:

- 1 82. (New) A method of roasting coffee beans comprising the steps of:
- 2 establishing the degree to which the coffee beans must be roasted to attain a
- 3 desired aroma;
- 4 generating a measurable first parameter which is indicative that the coffee beans
- 5 have been sufficiently roasted to yield the desired aroma;
- 6 storing the first parameter; roasting fresh coffee beans at a roasting temperature
- 7 by flowing heated air over the fresh coffee beans;
- 8 filtering substantially all pollutants from the heated air following the roasting
- 9 step;
- 10 thereafter reheating and recirculating a major portion of the substantially
- 11 pollutant-free air over the fresh coffee beans to thereby continue roasting;
- 12 cooling a minor portion of the filtered air to no more than about 115° F and
- 13 discharging the cooled minor portion of the air into an interior of a building frequented by
- 14 humans while reheating and recirculating the major portion of the air for further use during
- 15 roasting;
- 16 monitoring a second parameter which is compatible with the first parameter and is
- 17 generated by the fresh coffee beans during roasting;
- 18 upon detecting a match between the first and second parameters, discontinuing the
- 19 roasting step; and.

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

20 wherein the steps of roasting, filtering, reheating, recirculating, cooling and  
21 discharging are simultaneously and continuously performed while roasting is in progress.

1 83. (New) A method according to claim 82 wherein the first parameter is one  
2 of the color and darkness of the coffee beans and the second parameter is one of the color and  
3 darkness of the fresh coffee beans during roasting.

1 84. (New) A method according to claim 82 wherein the steps of roasting,  
2 filtering, reheating, recirculating, cooling and discharging are simultaneously and continuously  
3 performed while roasting is in progress;  
4 including adjusting the step of discontinuing the roasting of the fresh coffee beans  
5 as a function of at least one of the roasting temperature and atmospheric pressure.

1 85. (New) A method according to claim 82 wherein the step of monitoring  
2 comprises making a spectral analysis of the fresh coffee beans during the roasting step.

1 86. (New) A method according to claim 85 wherein the step of making a  
2 spectral analysis comprises directing a laser beam onto the fresh coffee beans during the roasting  
3 step.

1 87. (New) A method according to claim 86 wherein the laser beam has a  
2 wavelength in the range of between about 600 to 800 nm.

1 88. (New) A method according to claim 82 further comprising the steps of  
2 providing a multiplicity of different coffee bean types, establishing and storing the first  
3 parameter for each coffee bean type, prior to the roasting step selecting one of the multiplicity of  
4 coffee bean types for roasting; and wherein the step of discontinuing is carried out when there is  
5 a match between the first parameter for the selected coffee bean type and the second parameter.

1 89. (New) A method according to claim 88 further comprising the step of  
2 establishing a plurality of first parameters for at least one of the multiplicity of coffee bean types,  
3 each of which defines a different degree to which the coffee beans must be roasted to attain

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

4 correspondingly differing desired aromas; prior to the roasting step selecting one of the plurality  
5 of first parameters for the at least one coffee bean type; and wherein the step of discontinuing is  
6 performed when the second parameter matches the selected one of the first parameters.

1 90. (New) A method of automatically roasting coffee beans to attain a  
2 predetermined, desired coffee aroma, the method comprising the steps of:  
3 roasting a sample of the beans to a degree at which coffee made with the beans  
4 exhibits the desired aroma;  
5 sensing one of a color and a darkness of the beans when the beans have reached  
6 the degree of roasting and from the sensed color or darkness generating a first parameter which is  
7 indicative of the sensed color or darkness of the bean sample;  
8 storing the first parameter; thereafter roasting a batch of more than one pound of  
9 fresh beans by flowing heated air over the fresh beans;  
10 cleaning the heated air after it has passed the fresh beans so that the air is  
11 substantially pollutant-free;  
12 cooling the air after the air has passed the fresh beans to no more than about  
13 115° F while continuing flowing the heated air over the fresh beans;  
14 discharging the cooled, pollutant-free air into a substantially closed room  
15 frequented by humans;  
16 monitoring one of the color and darkness of the fresh beans being roasted and  
17 generating a second parameter which is indicative of a color or darkness of the fresh beans;  
18 comparing the first and second parameters during roasting of the fresh beans;  
19 terminating the roasting of the fresh beans when the first and second parameters  
20 match; and  
21 wherein the steps of roasting, cleaning, cooling and discharging are  
22 simultaneously and continuously performed while roasting is in progress.

1 91. (New) A method for uniformly roasting coffee beans at a plurality of  
2 geographically separate locations, the method comprising:

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

3 placing a roasting machine at each location inside an enclosed room frequented by  
4 humans;  
5 equipping each roasting machine with a roasting container for holding fresh beans  
6 while the beans are being roasted, a hot air supply for heating the fresh beans to a roasting  
7 temperature, and an air removal system for directing used air away from the container;  
8 removing from the used air substantially all debris, smoke, oil, and other  
9 pollutants in a filtration system;  
10 after the step of removing, cooling the used air, discharging the at least a portion  
11 of the cooled air into the enclosed room while continuing heating the fresh beans;  
12 recirculating a remaining portion of the cooled air to the hot air supply;  
13 directing a laser light beam of a frequency in the range of between about 600-800  
14 nm onto the beans in the container during roasting;  
15 generating an output signal from laser light reflected by the beans which is a  
16 function of the observed darkness of the beans;  
17 providing each roasting machine with a computer including a memory; feeding  
18 the output signal to the computer;  
19 at a central control station determining an optimal darkness for each bean type  
20 that will be roasted by the roasting machines;  
21 at the control station generating a control signal which reflects the optimal  
22 darkness of each roasted bean type;  
23 downloading the control signal from the central control station to the computer of  
24 each roasting machine;  
25 during roasting at any given roasting machine comparing the control signal stored  
26 in the associated memory with the output signal generated by the instrument; when the compared  
27 signals match, generating a command signal; and  
28 using the command signal to terminate the roasting of the beans in the container;  
29 wherein the steps of removing, cooling, discharging and recirculating are  
30 simultaneously and continuously performed while roasting is in progress.

Appl. No. 09/187,472  
Amdt. dated [insert date]  
Reply to Office Action of April 19, 2002

PATENT

1           92. (New) A method according to claim 91 further comprising the steps of:  
2           keeping an inventory of fresh beans proximate each roasting machine;  
3           monitoring the size of the fresh bean inventory;  
4           generating a low-inventory signal when the fresh bean inventory drops below a  
5   predetermined level;  
6           transmitting the inventory control signal to the central control station; and  
7           transferring additional fresh beans to the roasting machine which generated the  
8   low-inventory signal upon receipt thereof at the control station.

1           93. (New) A method according to claim 91 wherein each roasting machine  
2   has a plurality of different fresh bean types which can be roasted and wherein the method further  
3   comprises the steps of:  
4           generating an optimal darkness signal for each bean type at the control station;  
5           downloading each darkness signal to the computers of the roasting machines of the system; and,  
6           during roasting at any given one of the roasting machines, comparing the output  
7   signal from the instrument with the stored darkness signal which corresponds to the bean type  
8   being roasted in the container.

1           94. (New) A method of roasting coffee beans comprising the steps of:  
2           establishing the degree to which the coffee beans must be roasted to attain a  
3   desired aroma;  
4           generating a measurable first parameter which is indicative that the coffee beans  
5   have been sufficiently roasted to yield the desired aroma;  
6           storing the first parameter;  
7           roasting a batch of more than one pound of fresh coffee beans at a roasting  
8   temperature by flowing heated air over the fresh coffee beans;  
9           while flowing heated air over the fresh coffee beans, removing substantially all  
10   pollutants from the air downstream of the fresh coffee beans being heated in a filtration system,  
11   cooling at least a portion of the air downstream of the fresh coffee beans to no more than about

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

12 115° F, and thereafter, while continuing to flow heated air over the fresh coffee beans,  
13 exhausting the cooled air directly into a room of a building without recirculating any part of the  
14 cooled air into the filtration system;  
15 monitoring a second parameter which is compatible with the first parameter and is  
16 generated by the fresh coffee beans during roasting; and,  
17 upon detecting a match between the first and second parameters, discontinuing the  
18 roasting step.

1 95. (New) A method according to claim 94 wherein the first parameter is one  
2 of the color and darkness of the coffee beans and the second parameter is one of the color and  
3 darkness of the fresh coffee beans during the roasting step.

1 96. (New) A method according to claim 94 including adjusting the step of  
2 discontinuing the roasting of the fresh coffee beans as a function of at least one of the roasting  
3 temperature and atmospheric pressure.

1 97. (New) A method according to claim 94 wherein the step of monitoring  
2 comprises making a spectral analysis of the fresh coffee beans during the roasting step.

1 98. (New) A method according to claim 97 wherein the step of making a  
2 spectral analysis comprises directing a laser beam onto the fresh coffee beans during the roasting  
3 step.

1 99. (New) A method according to claim 98 wherein the laser beam has a  
2 wavelength in the range of between about 600 to 800 nm.

1 100. (New) A method according to claim 99 further comprising the steps of  
2 providing a multiplicity of different coffee bean types, establishing and storing the first  
3 parameter for each coffee bean type, prior to the roasting step selecting one of the multiplicity of  
4 coffee bean types for roasting; and wherein the step of discontinuing is carried out when there is  
5 a match between the first parameter for the selected coffee bean type and the second parameter.

Appl. No. 09/187,472  
Amdt. dated [insert date]  
Reply to Office Action of April 19, 2002

PATENT

1           101. (New) A method according to claim 100 further comprising the step of  
2     establishing a plurality of first parameters for at least one of the multiplicity of coffee bean types,  
3     each of which defines a different degree to which the coffee beans must be roasted to attain  
4     correspondingly differing desired aromas; prior to the roasting step selecting one of the plurality  
5     of first parameters for the at least one coffee bean type; and wherein the step of discontinuing is  
6     performed when the second parameter matches the selected one of the first parameters.

1           102. (New) A method of roasting coffee beans comprising the steps of:  
2                 establishing the degree to which the coffee beans must be roasted to attain a  
3     desired aroma by determining a first parameter which comprises at least one of a color and a  
4     degree of darkness which the coffee beans must have to yield the desired aroma;  
5                 generating at least one second parameter which reflects a predetermined  
6     development of the first parameter during a roasting of the coffee beans;  
7                 storing the parameters;  
8                 roasting fresh coffee beans at a roasting temperature;  
9                 monitoring the first parameter during roasting and discontinuing the roasting step  
10    when the coffee beans reaches the first parameter;  
11                 monitoring the at least one second parameter during roasting; and  
12                 adjusting the roasting step when the second parameter indicates that a deviation  
13    from the predetermined development of the first parameter occurred to thereby reestablish the  
14    predetermined development of the second parameter.

1           103. (New) A method according to claim 102 wherein the second parameter  
2     comprises at least one of the roasting temperature and atmospheric pressure.

1           104. (New) A method according to claim 102 wherein the step of monitoring  
2     the first parameter comprises directing a laser beam onto the fresh coffee beans during the  
3     roasting step.

Appl. No. 09/187,472  
Amdt. dated [insert date]  
Reply to Office Action of April 19, 2002

PATENT

1                   105. (New) A method according to claim 104 wherein the laser beam has a  
2 wavelength in the range of between about 600 to 800 nm.

1                   106. (New) A method according to claim 102 further comprising the steps of  
2 providing a multiplicity of different coffee bean types, establishing and storing the first  
3 parameter for each coffee bean type, prior to the roasting step selecting one of the multiplicity of  
4 coffee bean types for roasting; and wherein the step of discontinuing is carried out when the  
5 coffee beans reach the first parameter for the selected coffee bean type.

1                   107. (New) A method according to claim 106 further comprising the step of  
2 establishing a plurality of first parameters for at least one of the multiplicity of coffee bean types,  
3 each of which defines a different degree to which the coffee beans must be roasted to attain  
4 correspondingly differing desired aromas; prior to the roasting step selecting one of the plurality  
5 of first parameters for the at least one coffee bean type; and wherein the step of discontinuing is  
6 performed when the coffee beans reach the selected one of the first parameters.

1                   108. (New) A method according to claim 102 wherein the roasting step  
2 comprises flowing heated air over the fresh coffee beans, and including the steps of removing  
3 substantially all pollutants from the air downstream of the fresh coffee beans being heated,  
4 cooling the air downstream of the fresh coffee beans to no more than about 115° F, and thereafter  
5 exhausting the cooled air into an enclosed room of a building.

1                   109. (New) A method according to claim 102 wherein the step of roasting  
2 includes flowing heated air over the fresh coffee beans, and including the steps of filtering  
3 substantially all pollutants from the heated air following the roasting step, thereafter reheating  
4 and recirculating a major portion of the substantially pollutant-free air over the fresh coffee  
5 beans to thereby continue the roasting step; and discharging a minor portion of the filtered air  
6 prior to reheating and recirculating the major portion of the air.



Appl. No. 09/187,472  
Amdt. dated [insert date]  
Reply to Office Action of April 19, 2002

PATENT

1                    110. (New) A method of roasting coffee beans in a supermarket located inside  
2 a building, the method comprising the steps of:  
3                    establishing the degree to which the coffee beans must be roasted to attain a  
4 desired aroma;  
5                    generating a measurable first parameter which is indicative that the coffee beans  
6 have been sufficiently roasted to yield the desired aroma;  
7                    storing the first parameter; roasting fresh coffee beans at a roasting temperature  
8 by flowing heated air over the fresh coffee beans;  
9                    while flowing heated air over the fresh coffee beans removing substantially all  
10 pollutants from the air downstream of the fresh coffee beans being heated, cooling the air  
11 downstream of the fresh coffee beans to no more than about 115° F, and thereafter, while  
12 continuing to flow heated air over the fresh coffee beans, exhausting the cooled air into the  
13 supermarket;  
14                    monitoring a second parameter which is compatible with the first parameter and is  
15 generated by the fresh coffee beans during roasting; and,  
16                    upon detecting a match between the first and second parameters, discontinuing the  
17 roasting step.

Cal  
1                    111. (New) A method of automatically roasting coffee beans to attain a  
2 predetermined, desired coffee aroma, the method comprising the steps of:  
3                    roasting a sample of the beans inside a supermarket to a degree at which coffee  
4 made with the beans exhibits the desired aroma;  
5                    sensing one of a color and a darkness of the beans when the beans have reached  
6 the degree of roasting and from the sensed color or darkness generating a first parameter which is  
7 indicative of the sensed color or darkness of the bean sample; storing the first parameter;  
8                    thereafter roasting fresh beans by flowing heated air over the fresh beans;  
9                    cleaning the heated air after it has passed the fresh beans so that the air is  
10 substantially pollutant-free;

Appl. No. 09/187,472  
Amdt. dated February 11, 2004  
Reply to Office Action of April 19, 2002

PATENT

- 11 cooling the air after the air has passed the fresh beans to no more than about  
12 115° F while continuing flowing the heated air over the fresh beans;  
13 discharging the cooled, pollutant-free, room temperature air into the supermarket;  
14 monitoring one of the color and darkness of the fresh beans being roasted and generating a  
15 second parameter which is indicative of a color or darkness of the fresh beans; and  
16 comparing the first and second parameters during roasting of the fresh beans; and  
17 terminating the roasting of the fresh beans when the first and second parameters match.
-